according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Product code : 5987 014 111

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Detergent, Cleaning agent Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Würth Industrie Service GmbH & Co. KG

Drillberg, Industriepark Würth 97980 Bad Mergentheim

E-mail address of person

responsible for the SDS

prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling

EUH210 Safety data sheet available on request.

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version Revision Date: SDS Number: Date of last issue: 25.05.2022 1.4 10.11.2022 7609293-00005 Date of first issue: 25.11.2020

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
3-Butoxypropan-2-ol	5131-66-8	Skin Irrit. 2; H315	>= 1 - < 10
	225-878-4	Eye Irrit. 2; H319	
	603-052-00-8		
	01-2119475527-28		
Substances with a workplace exposure limit :			
(2-Methoxymethylethoxy)propanol	34590-94-8		>= 1 - < 10
	252-104-2		
	01-2119450011-60		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention.

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid inhalation of vapour or mist.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version Revision Date: SDS Number: Date of last issue: 25.05.2022 1.4 10.11.2022 7609293-00005 Date of first issue: 25.11.2020

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep in properly labelled containers. Store in accordance with

the particular national regulations.

Advice on common storage No special restrictions on storage with other products.

Storage class (TRGS 510) 12

Storage period 24 Months

Recommended storage tem- : > 5 °C

perature

7.3 Specific end use(s)

Specific use(s) No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2,2',2"-	102-71-6	AGW (Inhalable	1 mg/m3	DE TRGS
Nitrilotriethanol		fraction)	_	900
	Peak-limit: excursion factor (category): 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
(2-	34590-94-8	TWA	50 ppm	2000/39/EC
Methoxymeth- ylethoxy)propanol	0.000 0.10		308 mg/m3	2000/00/20
771	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW (Vapour	50 ppm	DE TRGS
		and aerosols)	310 mg/m3	900
	Peak-limit: excursion factor (category): 1;(I)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2',2"-Nitrilotriethanol	Workers	Skin contact	Long-term systemic effects	6,3 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	5 mg/m3
	Workers	Inhalation	Long-term systemic effects	5 mg/m3

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

	Consumers	Ingestion	Long-term systemic effects	13 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	3,1 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	1,25 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1,25 mg/m3
(2- Methoxymethyleth- oxy)propanol	Workers	Inhalation	Long-term systemic effects	308 mg/m3
	Workers	Skin contact	Long-term systemic effects	238 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	37,2 mg/m3
	Consumers	Skin contact	Long-term systemic effects	121 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg bw/day
3-Butoxypropan-2-ol	Workers	Inhalation	Long-term systemic effects	270,5 mg/m3
	Workers	Skin contact	Long-term systemic effects	44 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33,8 mg/m3
	Consumers	Skin contact	Long-term systemic effects	16 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	8,75 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2',2"-Nitrilotriethanol	Fresh water	0,32 mg/l
	Marine water	0,032 mg/l
	Intermittent use/release	5,12 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1,7 mg/kg dry weight (d.w.)
	Marine sediment	0,17 mg/kg dry weight (d.w.)
	Soil	0,151 mg/kg dry weight (d.w.)
(2-	Fresh water	19 mg/l
Methoxymethylethoxy)propanol		
	Freshwater - intermittent	190 mg/l
	Marine sediment	1,9 mg/l
	Sewage treatment plant	4168 mg/l
	Fresh water sediment	70,2 mg/kg dry weight (d.w.)
	Marine sediment	7,02 mg/kg dry weight (d.w.)
	Soil	2,74 mg/kg dry

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

		weight (d.w.)
3-Butoxypropan-2-ol	Fresh water	0,525 mg/l
	Marine water	0,0525 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	2,36 mg/kg
	Marine sediment	0,236 mg/kg
	Soil	0,16 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety glasses

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 60 min
Glove thickness : 0,35 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : clear

Odour : characteristic

Odour Threshold : No data available

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version 1.4

Revision Date: 10.11.2022

SDS Number: 7609293-00005

Date of last issue: 25.05.2022 Date of first issue: 25.11.2020

Melting point/freezing point :

Initial boiling point and boiling :

range

100 °C

0°C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 8,3 - 10,3

Concentration: 100 %

Viscosity

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : 23 hPa (20 °C)

Density : 1,005 - 1,015 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

exposure Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

3-Butoxypropan-2-ol:

Acute oral toxicity : LD50 (Rat): 3.300 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 3,52 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version Revision Date: SDS Number: Date of last issue: 25.05.2022 1.4 10.11.2022 7609293-00005 Date of first issue: 25.11.2020

(2-Methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 1,667 mg/l

Exposure time: 7 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 9.510 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

3-Butoxypropan-2-ol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

(2-Methoxymethylethoxy)propanol:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

3-Butoxypropan-2-ol:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 7 days

(2-Methoxymethylethoxy)propanol:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

3-Butoxypropan-2-ol:

Test Type : Buehler Test Exposure routes : Skin contact

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

(2-Methoxymethylethoxy)propanol:

Test Type : Human repeat insult patch test (HRIPT)

Exposure routes : Skin contact Species : Humans Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

3-Butoxypropan-2-ol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

(2-Methoxymethylethoxy)propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: Saacharomyces cerevisiae, miotic recombination

assay (in vitro) Result: negative

Carcinogenicity

Not classified based on available information.

Components:

3-Butoxypropan-2-ol:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years

Method : OECD Test Guideline 453

Result : negative

Remarks : Based on data from similar materials

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

(2-Methoxymethylethoxy)propanol:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years

Method : OECD Test Guideline 453

Result : negative

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

3-Butoxypropan-2-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

(2-Methoxymethylethoxy)propanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)
Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

3-Butoxypropan-2-ol:

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

Species : Rat

NOAEL : 350 mg/kg

LOAEL : 1.000 mg/kg

Application Route : Ingestion

Exposure time : 13 Weeks

Method : OECD Test Guideline 408

(2-Methoxymethylethoxy)propanol:

Species : Rat NOAEL : 1,21 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Species : Rat

NOAEL : 1.000 mg/kg
Application Route : Ingestion
Exposure time : 4 Weeks

Species : Rabbit
NOAEL : 2.850 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

3-Butoxypropan-2-ol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 560 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version Revision Date: SDS Number: Date of last issue: 25.05.2022 10.11.2022 7609293-00005 Date of first issue: 25.11.2020 1.4

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): >

1.000 mg/l

Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 560

mg/l

Exposure time: 96 h

EC50 : > 1.000 mg/lToxicity to microorganisms

Exposure time: 3 h

Method: OECD Test Guideline 209

(2-Methoxymethylethoxy)propanol:

Toxicity to fish LC50 (Poecilia reticulata (guppy)): > 1.000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.919 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 969

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 969

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 (Pseudomonas putida): 4.168 mg/l Toxicity to microorganisms

Exposure time: 18 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOEC: >= 0.5 mg/lExposure time: 22 d

ic toxicity) Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

3-Butoxypropan-2-ol:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 90 % Exposure time: 28 d

Method: OECD Test Guideline 301E

(2-Methoxymethylethoxy)propanol:

Biodegradability Result: Readily biodegradable.

Biodegradation: 76 %

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version 1.4 Revision Date: 10.11.2022

SDS Number: 7609293-00005

Date of last issue: 25.05.2022 Date of first issue: 25.11.2020

Exposure time: 28 d

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

3-Butoxypropan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: 1,2

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n-

octanol/water

: log Pow: 0,004

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.05.2022

 1.4
 10.11.2022
 7609293-00005
 Date of first issue: 25.11.2020

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

20 01 30, detergents other than those mentioned in 20 01 29

unused product

20 01 30, detergents other than those mentioned in 20 01 29

uncleaned packagings 15 01 06, mixed packaging

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version Revision Date: SDS Number: Date of last issue: 25.05.2022
1.4 10.11.2022 7609293-00005 Date of first issue: 25.11.2020

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

High : Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

WGK 1 slightly hazardous to water

ny)

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 4,15 %, 41,9 g/l

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version Revision Date: SDS Number: Date of last issue: 25.05.2022 1.4 10.11.2022 7609293-00005 Date of first issue: 25.11.2020

Remarks: VOC content excluding water

Regulation (EC) No. : less than 5 %: Anionic surfactants, Non-ionic surfactants, Pol-

648/2004, as amended ycarboxylates

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H315 : Causes skin irritation. H319 : Causes serious eye irritation.

Full text of other abbreviations

Eye Irrit. : Eye irritation Skin Irrit. : Skin irritation

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2000/39/EC / TWA : Limit Value - eight hours DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

according to Regulation (EC) No. 1907/2006



SSTCLNR-MELAG-CHAMBER-PROTECT-500ML

Version Revision Date: SDS Number: Date of last issue: 25.05.2022 1.4 10.11.2022 7609293-00005 Date of first issue: 25.11.2020

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN