

according 1907/2006/EG, Article 31

Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

No further relevant information available.

Wax adhesive

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Tradename: Wax adhesive

1.2 Relevant identified uses of the substance or

mixture and uses advised against:

Application of the substance / the mixture: Auxiliary for dental technology

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: al dente Dentalprodukte GmbH

Street / mailbox:

Country code. / postal code / city:

Phone:

0 53 21 / 80031

Fax:

0 53 21 / 50881

E-mail / Website: <u>info@aldente.de</u> / <u>www.aldente.de</u>

Further information obtainable from: al dente Dentalprodukte GmbH

1.4 Emergency telephone number

al dente Dentalprodukte GmbH: +49 (0) 53 21 / 80031 (Mon-Fri. 8 a.m. – 4 p.m.)

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Flam. Liq. 2 H225 Highly flammable liquid and vapour. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No

1272/2008:

Hazard pictograms:

The product is classified and labelled according to the CLP

regulation.





GHS02 GHS07

Signal word: Danger

Hazard-determining components of labelling: methyl acetate

n-butyl acetate

Hazard statements:

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information: Contains 2-(2-aminoethylamino)ethanol. May produce an

allergic reaction.

Labelling of packages where the contents do not exceed 125 ml Hazard pictograms







according 1907/2006/EG, Article 31

Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

Wax adhesive

GHS02 GHS07

Signal word: Danger

Hazard-determining components of labelling: methyl acetate

n-butyl acetate

Hazard statements: Void

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non-hazardous

additions.

Dangerous components:		
CAS: 79-20-9	methyl acetate	25-50%
EINECS: 201-185-2	<b>⊗</b> FI	
Index number: 607-021-00-X	Flam. Liq. 2, H225;	
RTECS: AI 9100000		
CAS: 123-86-4	n-butyl acetate	10-25%
EINECS: 204-658-1	<b>8</b>	
Index number: 607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336	
RTECS: AF 7350000		
CAS: 141-78-6	ethanol	10-25%
EINECS: 205-500-4	(A) = 1	
Index number: 603-002-00-5	Flam. Liq. 2, H225;	
RTECS: KQ 6300000		
Reg.nr.: 01-2119457610-43-		
XXXX		
CAS: 111-41-1	2-(2-aminoethylamino)ethanol	≤2.5%
EINECS: 203-867-5	(A) D (10000) (A) (A) (A) (A) (A) (A) (A) (A) (A) (A	
Index number: 603-194-00-0	Repr. 1B, H360Df; Skin Corr. 1B, H314; Skin Sens.	
RTECS: KJ 6300000	1, H317	
	Spezifische Konzentrationsgrenze:	
	STOT SE 3; H335: C ≥ 5 %	

Additional information:

For the wording of the listed hazardphrases refer to section

#### **SECTION 4: First aid measures**

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. If

symptoms persist, consult a doctor.

4.2 Most important symptoms and effects, both

acute and delayed:

After swallowing:

If symptoms persist consult doctor. No further relevant information available.

Page 3 of 8

according 1907/2006/EG, Article 31

Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

Wax adhesive

Indication of any immediate medical attention No further relevant information available. and special treatment needed:

**SECTION 5: Firefighting measures** 

Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water

Water with full jet.

spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing

5.2 Special hazards arising from the substance or No further relevant information available.

mixture:

5.3 Advice for firefighters

Protective equipment: No special measures required.

**SECTION 6: Accidental release measures** 

Personal precautions, protective equipment Use respiratory protective device against the effects of and emergency procedures: fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter drainage system, surface or ground

water.

6.3 Methods and material for containment and

cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid

binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections: See Section 7 for information on safe handling.

See Section 8 for information on personal protection

equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage** 

Precautions for safe handling

Keep receptacles tightly sealed. Information about protection against

Fumes can combine with air to form an explosive mixture.

explosions and fires: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and

receptacles:

Store in a cool location. Store only in the original receptacle.

Information about storage in one common

storage facility:

Not required.

Further information about storage conditions:

Keep container tightly sealed. Store in cool, dry conditions in

well-sealed receptacles.

Specific end use(s) No further relevant information available.

**SECTION 8: Exposure controls/personal protection** 

Control parameters

Additional information about design of

No further data; see item 7.

technical facilities:

Ingredients with limit values that require monitoring at the workplace:		
79-20-9	methyl acetate	
WEL	Short-term value: 770 mg/m³, 250 ppm	
	Long-term value: 616 mg/m³, 200 ppm	
123-86-	-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m³, 150 ppm	
64-17-5	ethanol	
W/FI	Long-term value: 1920 mg/m³ 1000 ppm	



according 1907/2006/EG, Article 31

Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

Wax adhesive

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls:

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eves.

Avoid contact with the eyes and skin.

Respiratory protection: Protection of hands:

Not required.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and

the degradation

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to

be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Rubber gloves.

For the permanent contact in work areas

without heightened risk of injury (e.g. Laboratory) gloves made of

the following material are suitable:

For the permanent contact gloves made of

the following materials are suitable:

As protection from splashes gloves made of

the following materials are suitable:

Eye protection:

Neoprene gloves

Nitrile rubber, NBR Butyl rubber, BR

Tightly sealed goggles.



# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Fluid

Colour: Transparent
Odour: Ester-like
Odour threshold: Not determined.
pH-value: Not determined.

Change in condition

Melting point/freezing point Undetermined.

Initial boiling point and boiling range: 57 °C Flash point: -13 °C

Flammability (solid, gas):

Not applicable.

Ignition temperature: 370 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not self-igniting.

Explosive properties: Product is not explosive. However, formation of explosive



according 1907/2006/EG, Article 31

Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

Wax adhesive

air/vapour mixtures are possible.

Explosion limits:

Lower: 1.2 Vol % Upper: 16 Vol % Vapour pressure at 20 °C: 220 hPa Density at 20 °C: 0.92 g/cm3 Relative density: Not determined.

Vapour density: Not determined. Evaporation rate: Not determined.

Solubility in / Miscibility with water: Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

Solvent content:

Organic solvents: 83.0 % VOC (EC) 80 % Solids content: 17.4 %

9.2 Other information No further relevant information available.

**SECTION 10: Stability and reactivity** 

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: No further relevant information available. 10.5 Incompatible materials: No further relevant information available. No dangerous decomposition products known.

10.6 Hazardous decomposition products:

**SECTION 11: Toxicological information** 

11.1 Information on toxicological effects Acute toxicity:

Primary irritant effect: Skin corrosion/irritation:

Serious eye damage/irritation:

Respiratory or skin sensitisation:

Germ cell mutagenicity:

Carcinogenicity: Reproductive toxicity:

STOT-single exposure:

STOT-repeated exposure:

Aspiration hazard:

No decomposition if used according to specifications.

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met.

Causes serious eye irritation.

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

May cause drowsiness or dizziness.

No further relevant information available.

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information** 

12.1 Toxicity

Aquatic toxicity:

12.2 Persistence and degradability: 12.3 Bioaccumulative potential:

12.4 Mobility in soil:

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment):

slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach

ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment



according 1907/2006/EG, Article 31

Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

Wax adhesive

PBT: Not applicable. Not applicable. vPvB:

No further relevant information available. 12.6 Other adverse effects

**SECTION 13: Disposal considerations** 

13.1 Waste treatment methods

Must not be disposed of together with household garbage. Do Recommendation:

not allow product to reach sewage system.

European waste catalogue WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE 00 00 80 (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products) 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

**SECTION 14:Transport information** 

14.1 UN number

ADR, IMDG, IATA: UN1993

14.2 UN proper shipping name

1993FLAMMABLELIQUID, N.O.S. ADR:

(METHYL ACETATE, ETHYL ACETATE) FLAMMABLE LIQUID, N.O.S. (METHYL

ACETATE, ETHYL ACETATE)

14.3 Transport hazard class(es)

ADR, IMDG, IATA

IMDG, IATA:



Class: 3 Flammable liquids.

Label:

14.4 Packing group

ADR, IMDG, IATA: Ш

14.5 Environmental hazards

Marine pollutant:

14.6 Special precautions for user Warning: Flammable liquids.

Kemler Number: EMS Number: F-E,S-E Not applicable.

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code

Transport/Additional information:

**ADR** 

Limited quantities (LQ): 1L Excepted quantities (EQ): Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Transport category: Tunnel restriction code D/E

**IMDG** 

Limited quantities (LQ): 1L Code: E2 Excepted quantities (EQ):

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml



according 1907/2006/EG, Article 31

Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

Wax adhesive

UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S.

(METHYL ACETATE, ETHYL ACETATE), 3, II

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to Regulation (EC) No

GHS label elements

1272/2008:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients is listed. Seveso category: P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX

Conditions of restriction: 3

XVII:

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and

electronic equipment – Annex II

None of the ingredients is listed.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H360Df May damage the unborn child. Suspected of damaging fertility.

Recommended restriction of use: Product only for professional use

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par

chemin de fer (Regulations Concerning the International Transport of Dangerous Goods

by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

according 1907/2006/EG, Article 31

Page 8 of 8 Revision: 27.05.2021 Version number 3 Printing date: 07.06.2021

**Wax adhesive** 

Repr. 1B: STOT SE 3:

Reproductive toxicity – Category 1B Specific target organ toxicity (single exposure) – Category 3 \* Data compared to the previous version altered.